

产品名称: 7.4V3.2公斤微型数码舵机 Product Name: 7.4V3.2kg-cm Micro Digital Servo

产品型号 Item No: OCS-D008

1. 使用环境条件 Apply Environmental Condition

No.	Item	Specification
1-1	存储温度 Storage Temperature Range	-20°C~70°C
1-2	运行温度 Operating Temperature Range	-15°C~65°C

2. 测试环境 Standard Test Environment

No.	Item	Specification
2-1	温度 Temperature range	25°C ±5°C
2-2	湿度 Humidity range	65%±10%

3. 机械特性 Mechanical Specification

No.	Item	Specification
3-1	尺寸 Size	23.5*9*19.5 mm
3-2	重量 Weight	7.7 g no including accessory
3-3	齿轮类型 Gear type	Aluminium
3-6	机构极限角度 Limit angle	360°
3-7	轴承 Bearing	2 Ball bearings
3-8	出力轴 Horn gear spline	15T- φ3.85mm
3-9	摆臂 Horn type	Plastic, POM
3-10	外壳 Case	Aluminium CNC
3-11	舵机线 Connector wire	145mm ±5mm
3-12	马达 Motor	Coreless motor
3-13	防水性能 Water proof	No

4. 电气特性 Electrical Specification (Function of the Performance)

No.	工作电压 Operating Voltage Range	3.8 V	
4-1	空载速度 No load speed	0.14 sec/60°	
4-2	空载电流 Runnig current(at no load)	100 mA	
4-3	堵转扭矩 Peak stall torque	1.8 kg. cm	
4-4	堵转电流 Stall current	0.6 A	
No.	工作电压 Operating Voltage Range	6.0 V	7.4 V
4-1	空载速度 No load speed	0.09 sec/60°	0.07 sec/60°
4-2	空载电流 Runnig current(at no load)	150 mA	200 mA
4-3	堵转扭矩 Peak stall torque	2.6 kg. cm	3.2 kg. cm
4-4	堵转电流 Stall current	0.8 A	1.1 A

Note: "\*"definition is average value when the servo runing with no load



广州欧兹电子科技有限公司

产品规格书

Specification of Product

Page 2/2

产品名称: 7.4V3.2公斤微型数码舵机 Product Name: 7.4V3.2kg-cm Micro Digital Servo

产品型号 Item No: OCS-D008

5. 控制特性 Control Specification:

No.	Item	Specification
5-1	控制信号 Command signal	PWM
5-2	放大器类型 Amplifier type	Digital Controller
5-3	脉冲宽度范围 Pulse width range	500~2500 $\mu$ sec
5-4	中立位置 Neutral position	1500 $\mu$ sec
5-5	旋转角度 Running degree	90° (when 1000~2000 $\mu$ sec)
5-6	死区宽度 Dead band width	2 $\mu$ sec
5-7	旋转方向 Rotating direction	CCW (when 1000~2000 $\mu$ sec)

6. 外形图 The Drawings

